

EFP to fiber system A5

(Bidi SDI, Bidi CVBS, Bidi balanced audio, Data, Ethernet, Tally, Power output,)



Description:

The EFP to fiber system A5 with Bidi 3G/HD/SD-SDI video & Tally & Bidi Balanced Audio & Bidi CVBS & Bidi line level audio & 100M Ethernet & DC Power output Multiplexer that allow transport of pathological patterns high-definition video and CD audio high sampling rate 58khz over standard fiber optic networks. Only one dual fiber cable is needed to transmit all required signals for a remote camera and it's operator in both directions over kilometers.

The Live Connector Remote Camera Interface System is designed to handle news, sports, and other day-to-day remote interfacing needs with ease. Live Connector offers an advanced portable, single-mode optical interface for ENG and OB vans, SNG vehicles, and production trailers. Features include 3G/HD/SD-SDI video path, on-air and cue audio, intercom, remote, and Ethernet data. Uses two single-mode fibers and models are available with a variety of optical connectors. Live Connector is an ideal infrastructure solution for airports, studio complexes, arenas, and campus environments.

Benefits of the EFP to fiber system A5: (Item No.: EFP-A5)

- 1) 1x 3G-SDI, Bidi,
- 2) 1x CVBS, Bidi,
- 3) 1x Balanced audio, Bidi,
- 4) 1x Line level audio, Bidi,
- 5) 1x 100M Ethernet
- 6) 1x Tally
- 7) 1x DC 12V Power output
- 8) Dual ST Connection

Features:

- 1) Transmit 3G HD-SDI video and embedded audio over one fiber.
- 2) Support 270Mb/s to 2.97Gbit/s.
- 3) Broadcast Signal Quality, Compliance with SMPTE 424M, SMPTE 292M and SMPTE 259M.
- 4) Immune to pathological patterns over the entire link budget and operating temperature range.
- 5) Automatic cable EQ (Belden 1694A cable) to 100 meters at 3G HD-SDI transmission.
- 6) LED indicators.
- 7) Supports hot swapping and hot plugging.

Typical project:



Technical Performance list:	
Product Name:	EFP to Fiber System A5
Product Model:	Transmitter: EFP-A5-T, Receiver: EFP-A5-R
Optical Fiber:	Dual fibers, ST connector, Compatible with multimode or single mode fiber
Extend distance:	Up to 15km via single mode fiber optic cable
Working Environment:	Working Temperature: 0°C ~ +75°C; Relative Humidity: 0 ~ 95% (no cold condensation)
Dimension:	19" 1U rack mount on both end
Warranty:	2 Years warranty
Packing in the box:	1x Transmitter, 1x Receiver, 2x Power adapter,
Optical Performance:	
Fiber Connector:	Transmitter: 2x ST Receiver: 2x ST
Working Wavelength:	1310nm/1550nm
Return Loss:	> 15dB
Shake:	< 0.2UI
Electric Performance:	
Power adaptor:	AC 90-260V input, DC 12V1A output
MTBF:	> 100000 Hours