




New EFP to fiber converters

Date: 2021/3/21

File No.: Pro-210321-EFP

1	EFP-2ch Panasonic to fiber converter Lemo SMPTE 304	HK-EFP-BL1
2	EFP-4K to fiber converter Lemo SMPTE 304 (11.88Gbit/s)	HK-EFP-BL2
3	EFP-12G to fiber converter Lemo SMPTE 304 (11.88Gbit/s)	HK-EFP-BL3
4	EFP-Ikegami camera to fiber converter Lemo SMPTE 304	HK-EFP-BL4
5	EFP-JVC camera to fiber converter Lemo SMPTE 304	HK-EFP-BL5
6	EFP-Datavideo MCU control to fiber converter Lemo SMPTE 304	HK-EFP-BL6
7	EFP-SONY Camera to fiber converter Neutrik OpticalCON DUO	HK-EFP-BN7

SN	Product and Description	Pictures
1	<p>EFP-2ch Panasonic to fiber converter Lemo SMPTE 304</p> <ul style="list-style-type: none"> - 2ch forward SDI to fiber broadcast live shooting - SDI 2ch forward + 1ch return - Tally 1ch - BB/TC 1ch - Intercom to main station Balanced audio - Ethernet 10/100M - PGM 1ch - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE 424M, SMPTE 292M, SMPTE 259M, up to 3Gbit/s 	
2	<p>EFP-4K to fiber converter Lemo SMPTE 304 (11.88Gbit/s)</p> <ul style="list-style-type: none"> - SDI 1ch 4K/12G-SDI+1ch reverse 3G/HD-SDI - Remote control Sony - Tally 1ch - BB/TC 1ch - Intercom to main station Party line audio - Ethernet 10/100M - IFB reverse balanced audio - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE ST-2082, ST-2081, 424M, 344M, 292M, 259M, DVB-ASI, 	
3	<p>EFP-12G to fiber converter Lemo SMPTE 304 (11.88Gbit/s)</p> <ul style="list-style-type: none"> - SDI 1ch 4K/12G-SDI+1ch reverse 3G/HD-SDI - Remote control Sony - Tally Datavideo tally - BB/TC 1ch - Intercom to main station Datavideo's ITC - IFB reverse balanced audio - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE ST-2082, ST-2081, 424M, 344M, 292M, 259M, DVB-ASI, 	

<p>4</p>	<p>EFP-Ikegami camera to fiber converter Lemo SMPTE 304</p> <ul style="list-style-type: none"> - SDI 1ch forward + 1ch return - Remote control Ikegami - Tally 1ch - BB/TC 1ch - Intercom to main station Balanced audio - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE 424M, SMPTE 292M, SMPTE 259M, up to 3Gbit/s 	
<p>5</p>	<p>EFP-JVC camera to fiber converter Lemo SMPTE 304</p> <ul style="list-style-type: none"> - SDI 1ch forward + 1ch return - Remote control: JVC - Tally: 1ch - Intercom to main station: Party line audio - Ethernet: 10/100M - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE 424M, SMPTE 292M, SMPTE 259M, up to 3Gbit/s 	
<p>6</p>	<p>EFP-Datavideo MCU control to fiber converter Lemo SMPTE 304</p> <ul style="list-style-type: none"> - SDI 1ch forward + 1ch return - Remote control: Datavideo - Tally: 1ch - Genlock: 1ch - Intercom to main station: Party line audio - Ethernet: 10/100M - Optical connector: Lemo SMPTE 304 / Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE 424M, SMPTE 292M, SMPTE 259M, up to 3Gbit/s 	
<p>7</p>	<p>EFP-SONY Camera to fiber converter Neutrik OpticalCON DUO</p> <ul style="list-style-type: none"> - SDI 1ch forward + 1ch return - Remote control: SONY - Tally: 1ch - Genlock: 1ch - Intercom to main station: Balanced audio - PGM: 1ch - Optical connector: Neutrik OpticalCON DUO - Camera end can be rotated 90 degrees - Transmission Distance: 0-10km over Single-mode fiber - Support: SMPTE 424M, SMPTE 292M, SMPTE 259M, up to 3Gbit/s 	